



Technische Daten / Technical specifications			Anschlüsse / Connections		
Traglast axial statisch	Load axial static	160 [kN]	R1	1/2"	Drehen rechts / Rotating right
Traglast axial dynamisch	Load axial dynamic	70 [kN]	R2	1/2"	Drehen links / Rotating left
Drehmoment @ 320 bar	Torque @ 320 bar	2800 [Nm]	GO	1/2"	Greifer öffnen / Clamshell open
Drehzahl [U/min]	Rotation speed [rpm]	18 [1/min]	GS	1/2"	Greifer schliessen / Clamshell close
Betriebsdruck Drehen max	Rotating max	320 [bar]	GL	3/8"	Freie Leitung (Leckage) / Free line (leakage) max. 25 [bar]
Betriebsdruck Greifer max	Rotary feedthrough max	350 [bar]	<b>Ölfluss beim Drehen / Recommended flow</b>		
Gewicht	Weight	61 [kg]	Minimum:	6 [l/min]	
<b>Baggerdienstgewicht / Operating fields</b>			Optimal:	22 [l/min]	
Fest	Fixed connection	4000 - 6500 [kg]	Öldurchgang / Oil-supply (GO/GS)	60 [l/min]	
Kardanisch	Cardanic suspension	16000 [kg]			